



TECHNICAL DATA SHEET

HW88106 SHANKLIN HAND GRADE

USAGE: (SEE HAVWOODS QUICK REFERENCE GUIDE TO CHOOSING THE CORRECT FLOOR).



PRODUCT DETAILS

Product Code	HW88106
Product Range	Hand Grade
Construction	Engineered 3 layer
Specie	Oak, Birch Plywood, Oak
Pattern	1-Strip Plank
Process	Sculptured Surface
Finish	Hard Wax Oil Finish
Profile	T&G Ends Matched
Edge Profile	Rounded Edge
Top Layer	6mm (¼") Solid European Oak
Backing	Birch Plywood
Thickness	+/- 23mm (¾")
Width	Random: 280, 330, 380, 430, 480mm (11", 13", 15", 17", 19")
Length	2000-4000mm (Random: 78 ¾" - 157 ½")
Maintenance	Comprehensive maintenance instructions and materials are available from Havwoods Ltd. for all floors



INSTALLATION METHODS

Fully Bonded	Yes (Recommended)*
Nailed	Yes *
Floated on Underlay	No
Over Underfloor Heating	Yes*# (to be installed over Wet Underfloor Heating Systems only - Please see UFH Installation Guidelines for details)

GRADING CRITERIA

Maximum Size of Sound Knots	Unlimited Diameter Allowed
Maximum Size of Broken Knots	50mm (2") Diameter Allowed
Filled Defects	Allowed
Heart/Pith	Allowed
Sapwood	Face Side Allowed
End Checks	50% of Board Allowed (Max 5mm (¼") Open)
Insect damage	Not Allowed
Filler	Allowed
Color Variation	Rouge Allowed in Dark Colors Only
Inner Bark	Not Allowed

NB: The product grading criteria is an approximation. Please ask for details

TECHNICAL CRITERIA

Origin	Europe
Responsible Certification	FSC® Certified
Janka Hardness Rating	1,360 lbf (6,000N)
Formaldehyde Emission	E1/BLQ (0.01ppm) - CARB 2 Compliant
Pentachlorophenol Emission	< 5ppm
Slip Testing	82 PTV
Reaction to Fire Classification	Cfl-s1
Thermal Conductivity	0.17 W/mK

* Subject to compatible subfloor and correct installation (see Installation Guidelines) including sensors.
Temperature of top-face must never be allowed to exceed 27°C. UFH protocol to control temperature conditions is recommended.

INSTALLATION AND WARRANTY

All Havwoods floors must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Havwoods warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standard worldwide.

© This technical data sheet was written by Havwoods International. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. Imperial measurements are a translation from the metric; for the most accurate product measurements please follow the metric sizes. The photographs used in this sheet are intended only as illustrations. No rights can be derived from them.

